



TECHNICAL SPECIFICATIONS
US Version



Shown: PM 932ED with optional 7-Day Automatic On/Off Timer.

Project _____
Item No. _____
Quantity _____
Date _____

PM 93X Series
PM 931ED, PM 932ED, PM 933ED, PM 934ED, PM 935ED

PizzaMaster® Modular Electric Deck Oven

- The world's largest range of electric deck ovens.
- Trusted in 170+ countries and counting.
- Unmatched capacity. Unstoppable output.
- Precision baking made effortless.
- Built to last. Backed for life.

International Voltage
and Certifications
– Available upon request



Standard Features

✓ IQControl Panel™	✓ Dual Xenon Oven Deck Lights	✓ Lockable Casters on 1/2/3/4-Deck Ovens
✓ TempIQ Recovery™	✓ Vent Control Lever for Each Deck	✓ Multi-Functional Oven Stand
✓ TempIQ Guard™	✓ High-Density Insulation	✓ Disassemble Design 3/4/5-Deck Ovens Available as an option on 2-deck oven
✓ TurboStart	✓ Strong Ergonomic Oven Door Handles	✓ Resettable Overheat Protection
✓ Balanced Heat Distribution™	✓ Durable Long-Life Oven Door	✓ 1 & 3 Phase El. Power Supply Available
✓ 3 Heat Zones: Top, Bottom, Front	✓ Pull-Up Oven Door	✓ Flexible Power Supply for 480V Single or multiple incoming supply cables
✓ XTREME Performance™ 932°F	✓ Large Clear Window Glass Oven Door	✓ International Voltages & Certifications Available upon request
✓ Ceramic Clay Stones w/ Crisping Function Rec. for baking temperatures up to 700°F	✓ Stainless Steel Front	✓ Start-Up Maintenance Kit Includes: Oven bulbs Cleaning supplies
✓ Extended Ventilation Hood	✓ Ventilated Front	
✓ Sliding Unloading Shelf on 1/2/3-Deck Ovens 2 pcs included	✓ Bake Timer with Manual Shut-Off Alarm	
	✓ Single-Push Auto Bake Timer with Alarm	




Optional Features

○ Artisan High-Temperature Clay Stones Rec. for baking temperatures over 700°F	○ Extra High Deck Maximum baking temperature limited to 752°F	○ Side Shield Panel
○ Factory Direct Ventilation System Requires Extended Ventilation Hood	○ Power Guard™ Control system for limited power supply	○ Oil and Spice Rack Includes pizza cutter
○ 7-Day Automatic On/Off Timer	○ Marine Option Adapted for offshore installations	○ Pizza Tool Holder Holds up to 3 tools
○ Phantom Black Finish	○ Near Coastal Option Enhanced protection against saltwater	○ Pizza Tools Loading Peels (13, 14, 17.7 and 19.7 in) Turning Peels (7.9 and 9 in) Oven Brush Freestanding Peel Holder
○ Disassemble Design 2-Deck Oven	○ Fixed Unloading Shelf on 4-Deck Oven	
○ Lockable Casters for 5-Deck Oven	○ Side Shelf Maximum 2 per side	
○ Steam System Maximum baking temperature limited to 752°F		




One oven, multiple possibilities. Individually configured decks let you bake different products at once.
Example: **Deck 1** for Bakery, **Deck 2** for Standard Pizza, and **Deck 3** for High Temperature Pizza.

Technical Drawings




931
Front
Side
Rear






932
Front
Side
Rear






933
Front
Side
Rear





934
Front
Side
Rear





935
Front
Side
Rear



931 - 935
Top



931 - 935
Baking Surface
Stone size



Notes

- Required 2" minimum clearance on all sides.
- Optional Steam System: Measurement "K" includes the required minimum clearance.
- Oven must be installed on a flat horizontal surface.
- Installation next to a deep fryer, hub, pasta cooker or similar equipment requires an optional Side Shield Panel.
- Optional Extra High Deck does not change the oven exterior height in measurement "B".

External Dimensions

See page 2	Description		Unit	931	932	933	934	935
A	Oven Width		in	71,3	71,3	71,3	71,3	71,3
B	Total Oven Height	a) With Hood (standard)	in	64,9	71,6	74,9	78,2	86,4
		b) Without Hood	in	62,2	68,8	72,1	75,5	83,6
C1	Height to Baking Surface, Deck 1 ¹⁾	a) Standard Deck	in	49,5	42,8	32,8	22,8	17,6
		b) Extra High Deck (option) ²⁾	in	48,5	41,9	31,8	21,8	16,6
C2	Height to Baking Surface, Deck 2 ¹⁾	a) Standard Deck	in	-	56,2	46,1	36,1	30,9
		b) Extra High Deck (option) ²⁾	in	-	55,2	45,2	35,2	30,0
C3	Height to Baking Surface, Deck 3 ¹⁾	a) Standard Deck	in	-	-	59,5	49,5	44,3
		b) Extra High Deck (option) ²⁾	in	-	-	58,5	48,5	43,3
C4	Height to Baking Surface, Deck 4 ¹⁾	a) Standard Deck	in	-	-	-	62,8	57,6
		b) Extra High Deck (option) ²⁾	in	-	-	-	61,9	56,7
C5	Height to Baking Surface, Deck 5 ¹⁾	a) Standard Deck	in	-	-	-	-	71,0
		b) Extra High Deck (option) ²⁾	in	-	-	-	-	70,0
D1	Height to Bottom of Oven (standard)		in	43,4	36,7	26,7	16,7	11,5
D2	Height to Bottom of Oven (for 5-deck ovens with optional casters) ³⁾		in	-	-	-	-	7,2
E1	Height to Upper Sliding Shelf		in	40,2	33,5	23,5	-	-
E2	Height to Lower Sliding Shelf		in	8,3	8,3	8,3	-	-
E3	Height to Fixed Shelf (option for 4-deck ovens)		in	-	-	-	7,0	-
F	Shelf Width		in	65,6	65,6	65,6	65,6	65,6
G	Oven Depth, with Hood	a) Ventilation Hood (standard)	in	49,6	49,6	49,6	49,6	49,6
		b) Extended Ventilation Hood (option)	in	56,3	56,3	56,3	56,3	56,3
H	Oven Depth, without Hood		in	44,3	44,3	44,3	44,3	44,3
I	Depth of Sliding Shelf when Fully Extended		in	21,2	21,2	21,2	-	-
J	Depth with Handles	a) Closed door	in	46,7	46,7	46,7	46,7	46,7
		b) Open door	in	52,2	52,2	52,2	52,2	52,2
K	Depth of Steam System (option)		in	3,9	3,9	3,9	3,9	3,9
L1	Height Position for Electrical Supply, Decks 1-3 [± 1 in]		in	46,8	40,1	30,0	20,0	14,8
L2	Height Position for Electrical Supply, Decks 4-5 [± 1 in]		in	-	-	-	60,1	54,9
M	Width Position for Electrical Supply [± 2 in]		in	3,7	3,7	3,7	3,7	3,7
N	Height Position for Water Supply (with optional Steam System)		in	45,9	39,2	29,2	19,2	14,0
O	Width Position for Water Supply (with optional Steam System)		in	46,7	46,7	46,7	46,7	46,7
P	Depth Position for Front Ventilation (with Hood attached)		in	4,3	4,3	4,3	4,3	4,3
Q	Width Position for Front Ventilation (with Hood attached)		in	32,2	32,2	32,2	32,2	32,2
R	Depth Position for Rear Ventilation		in	4,8	4,8	4,8	4,8	4,8
S	Width Position for Rear Ventilation		in	3,5	3,5	3,5	3,5	3,5
T	Height of Casters Only (1 to 4 decks)		in	5,2	5,2	5,2	5,2	-
U	Height of Legs Only		in	38,2	31,5	21,5	11,5	11,5
V	Height of Oven Only	a) With Hood (standard)	in	21,5	34,9	48,2	61,6	74,9
		b) Without Hood	in	18,8	32,1	45,5	58,8	72,2

Note 1) Add +0,5" for optional Artisan High-Temperature Clay Stones.

Note 2) Optional Extra High Deck does not change the oven exterior height in measurement "B".

Note 3) All other heights are lowered by 4,3" with optional casters for 5-deck ovens.

Internal Dimensions

See page 2	Description	Unit	931	932	933	934	935
X1	Stone size, depth - Ceramic Clay Stone (standard)	in	36,2	36,2	36,2	36,2	36,2
X2	Stone size, depth - Artisan High-Temperature Clay Stone (option)	in	18,1	18,1	18,1	18,1	18,1
Y	Stone size, width	in	18,1	18,1	18,1	18,1	18,1
-	No. of Stones	a) Ceramic Clay Stone (standard)	pcs	3	3	3	3
		b) Artisan HT Clay Stone (option)	pcs	6	6	6	6
X1	Total baking surface, depth	in	36,2	36,2	36,2	36,2	36,2
Z	Total baking surface, width	in	54,3	54,3	54,3	54,3	54,3
-	Total baking surface, area	ft ²	13,7	13,7	13,7	13,7	13,7
-	Internal deck height	a) Standard Deck	in	8,3	8,3	8,3	8,3
		b) Extra High Deck (option)	in	9,6	9,6	9,6	9,6
-	Deck door opening height	a) Standard Deck	in	5,7	5,7	5,7	5,7
		b) Extra High Deck (option)	in	7,1	7,1	7,1	7,1

Packing Dimensions

Description		Unit	931	932	933	934	935
Net weight		lbs	694	1064	1448	1752	2089
Gross weight (total)		lbs	802	1179	1576	1881	2304
Size / Dimensions	a) Width	in	79	79	79	79	79
	b) Depth	in	55	55	55	55	55
	c) Height	in	29	39	53	66	83
Volume		ft³	73.2	97.9	132.5	166.1	209.6

Guidelines for choosing the right oven

1. Measure the available space for the oven.
2. Determine the maximum capacity need per hour and average bake time.
(See capacity tables for guidance).
3. Note that different bake temperatures require separate decks.
4. Factor in time needed for loading and unloading pizzas.
5. Consider potential future expansion plans and the need for additional decks.



OvenIQ
Configurator™

Capacity tables

Round pizza (in)	Capacity, per deck	Rectangular pizza (in)		Capacity, per deck
		Length	Width	
7	35	10	8	20
10	18	10	10	15
12	12	12	12	12
14	8	14	10	10
16	6	14	14	6
18	6	23,6	7,9	8
20	4	23,6	11,8	6
21	3	23,6	15,8	4
24	2	26	18	4

Electrical

Voltage	Parameters (Per deck, unless specified)		Unit	931	932	933	934	935
208 V 1 ph 50/60 Hz	Max. Current ¹⁾		Amps	80,8	81,0	81,3	81,5	81,7
	Average Current at normal operation		Amps	28,3	28,4	28,4	28,5	28,6
	Min. Breaker (Type C is rec.)		Amps	88,8	89,1	89,4	89,6	89,9
	Max. Power		kW	16,8	16,8	16,8	16,8	16,8
208 V 3 ph 50/60 Hz	Max. Current ¹⁾		Amps	46,8	46,8	46,9	47,2	47,4
	Average Current at normal operation		Amps	16,4	16,4	16,4	16,5	16,6
	Min. Breaker (Type C is rec.)		Amps	51,5	51,5	51,6	51,9	52,1
	Max. Power		kW	16,8	16,8	16,8	16,8	16,8
240 V 1 ph 50/60 Hz	Max. Current ¹⁾		Amps	76,2	76,5	76,7	76,9	77,1
	Average Current at normal operation		Amps	26,7	26,8	26,8	26,9	27,0
	Min. Breaker (Type C is rec.)		Amps	83,8	84,1	84,3	84,6	84,8
	Max. Power		kW	18,3	18,3	18,3	18,3	18,3
240 V 3 ph 50/60 Hz	Max. Current ¹⁾		Amps	44,2	44,2	44,3	44,5	44,7
	Average Current at normal operation		Amps	15,5	15,5	15,5	15,6	15,6
	Min. Breaker (Type C is rec.)		Amps	48,6	48,6	48,7	49,0	49,2
	Max. Power		kW	18,3	18,3	18,3	18,3	18,3
480 V 3 ph + N 50/60 Hz	Max. Current ¹⁾	a) Per deck	Amps	20,3	20,3	20,4	20,6	20,8
		b) Single cable	Amps	20,3	40,6	60,9	-	-
		c) Dual cables ²⁾	Amps	-	-	-	60,9 + 20,3	60,9 + 40,6
	Average Current at normal operation	a) Per deck	Amps	7,1	7,1	7,1	7,2	7,3
		b) Total (oven)	Amps	7,1	14,2	21,4	28,8	36,3
		a) Per deck	Amps	22,3	22,3	22,4	22,6	22,8
	Min. Breaker (Type C is rec.)	b) Total (oven)	Amps	22,3	44,7	67,3	90,6	114,2
		a) Per deck	kW	16,8	16,8	16,8	16,8	16,8
	Max. Power	b) Total (oven)	kW	16,8	33,6	50,4	67,2	84,0

Note 1) Only at start-up (~20 min) with activated TurboStart or all heat zones at max.

Note 2) First cable for decks 1-3; Second cable for decks 4-5.

Ventilation

EPA 202 Tested	931	932	933	934	935
PizzaMaster electric deck ovens conform to ventilation recommendations set forth by ANSI/NFPA96 using EPA 202 test method. Grease-laden vapor test, EPA 202 (ventless requirement): 8 hr, Pepperoni pizza, < 5,00 mg/m ³ .	✓	✓	✓	✓	-

How to install	Connection(s)				Air flow					
	Qty	Pos	Unit	Value	Unit	931	932	933	934	935
Factory Direct Vent. System (option) ¹⁾	1	Center	in	8	CFM	586	674	762	850	937
Direct Ventilation ²⁾	2	Front	in	6-1/2	CFM	586	674	762	850	937
		Rear	in	4	CFM	22	44	66	88	110
Under External Hood	-	-	-	-	CFM	439	505	571	637	703

Note 1) Requires Extended Ventilation Hood.

Note 2) For best performance, Extended Ventilation Hood is recommended.

Exhaust temperature (See page 3 for measurement "B/b")			
Connection	Unit	"B/b" + 16 in	"B/b" + 40 in
Center ¹⁾	°F	-	108
Front ²⁾	°F	115	108
Rear ²⁾	°F	239	228

Note 1) With optional Factory Direct Ventilation System.

Note 2) Without optional Factory Direct Ventilation System.

Heat emission ¹⁾						
Type	Unit	931	932	933	934	935
Total	BTU/h	20063	40127	60190	80254	100317
Sensible	BTU/h	5732	11465	17197	22930	28662
Latent	BTU/h	14331	28662	42993	57324	71655

Note 1) At normal operation, all decks running.

Water Only for Optional Steam System

Requirements	Value	Requirements	Value
Water drain	Not required	Connection	NH 3/4"
Backflow protection	Required, not included	General water quality	Cold Drinking Water
Auto shut-off valve	Included	Water softener	Recommended
Incoming water pressure	29 - 58 psi	Particle filter	Recommended

Water quality requirements	Unit	Value
Magnesium (Mg)	mg/l	< 30
Calcium (Ca)	mg/l	20 - 100
Hardness	dH	4,0 - 7,0
Acidity at 68°F	pH	7,5 - 8,5
Alkalinity (HCO ₃)	mg/l	> 60